## CSU ENVIRONMENTAL REVIEW CHECKLIST

2-3-125 PHYSICAL ENVIRONMENTAL REQUIREMENTS	Y	Ν	Comment
Bathrooms			
Ventilated			
Handicapped accessibility/grab bars			
1 shower per 8 individuals			
1 toilet and sink per 6 individuals			
Access to bathrooms not through another individual'			
bedroom			
Shower head recessed or non-weight bearing			
No weight bearing protrusions, over 30 lbs.			
Toilet flush-o-meter, no water tank or cover.			
Mirrors			
Polycarbonate mirror			
Fully secured			
Flush mounted			
Seclusion and Restraint Room			
Must be free of sharp edges/corners.			
Withstand physical abuse			
Up to 3 feet high around the room must be			
impermeable to body fluids.			
Where padded noncombustible material used.			
Minimum of 70 sq feet			
Ceiling must be at least 9 ft high.			
Any CSU with 36 beds or more must have two			
seclusion and restraint rooms			
S & R Bed			
Must be designed commercially for restraint.			
Must be bolted to the floor and without sharp edges.			
Must be impermeable to fluids.			
Must allow accessibility to lights, smoke detectors or			
items in the ceiling.			
Must be free of sharp edges/corners.			
Window			
Unbreakable			
Blind spots addressed.			
Fenced recreational area			
Enclosed with a minimum height of 6 feet.			
Privacy from public view.			
May be topped with a 45 degree inward slanting			
restraining wire using no sharp injurious material.			
Screening Area			
Adjacent to the waiting area			
One or more windows provide visual access to staff			
from a common area.			
Bedrooms			

Department of Behavioral Health and Developmental Disabilities Crisis Stabilization Unit Application and User's Guide for Licensure

Any furniture that is capable of barricading the door shall be secured to the wall		
No beds with springs, cranks, rails, wheels, rollaway, cots, bunks, stacked, hide-a-bed, and pull out couches Minimum of 60 sq ft per individual       Image: Constraint of the state of t	Any furniture that is capable of barricading the door	
cots, bunks, stacked, hide-a-bed, and pull out couches	shall be secured to the wall	
Minimum of 60 sq ft per individual	No beds with springs, cranks, rails, wheels, rollaway,	
Textured windows for privacy, non – weight bearing curtain or blinds       Image: Curtain or blinds         Additional Requirements       Image: Curtain or blinds         Locked storage for valuable and belongings of all individuals.       Image: Curtain or blinds         Laundry facilities provided for resident use.       Image: Curtain or blinds         Entrance, exits and sidewalks free of impediments.       Image: Curtain or blinds         1 operable non-pay phone.       Image: Curtain or blinds         1 drinking fountain per CSU accessible to all residents.       Image: Curtain or blinds         Hardware must be incapable of manipulation or removal.       Image: Curtain or blinds         Lighting fixtures must be recessed or tamper proof (ex. lexan).       Image: Curtain or blinds         Water temp maintained between 110-120 F degrees       Image: Curtain or blinds         (43-48 C)       Image: Curtain or blinds       Image: Curtain or blinds         Unbreakable mirrors.       Image: Curtain or blinds       Image: Curtain or blinds         82-3-1-23 Environment of Care       Image: Curtain or blinds       Image: Curtain or blinds         The ceilings and air distribution devices, light fixtures, myrinkler heads, and other apparatus shall be curable of swinging outward.       Image: Curtain or blinds         Blind spots addressed. unbreakable mirrors.       Image: Curtain or blinds       Image: Curtain or blinds         Doo	cots, bunks, stacked, hide-a-bed, and pull out couches	
Textured windows for privacy, non – weight bearing curtain or blinds       Image: Curtain or blinds         Additional Requirements       Image: Curtain or blinds         Locked storage for valuable and belongings of all individuals.       Image: Curtain or blinds         Laundry facilities provided for resident use.       Image: Curtain or blinds         Laundry facilities provided for resident use.       Image: Curtain or blinds         Laundry facilities provided for resident use.       Image: Curtain or blinds         I operable non-pay phone.       Image: Curtain or blinds         1 drinking fountain per CSU accessible to all residents.       Image: Curtain or blinds         Hardware must be incapable of manipulation or removal.       Image: Curtain or blinds         Lighting must be sufficient for reading.       Image: Curtain or blinds         Lighting fixtures must be recessed or tamper proof (ex. lexan).       Image: Curtain or blinds         Water temp maintained between 110-120 F degrees       Curtain or blinds         R32-31-23 Environment of Care       Image: Curtain or blinds         The ceilings and air distribution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.       Image: Curtain or blinds         Blind spots addressed. unbreakable mirrors.       Image: Curtain or blinds       Image: Curtain or blinds         Payable of swinging outward.       Imardware must be incapable of manipulation or	Minimum of 60 sq ft per individual	
curtain or blinds       Additional Requirements         Additional Requirements       Image: Constraint of the second secon		
Locked storage for valuable and belongings of all individuals.Locked storage for valuable and belongings of all individuals.Laundry facilities provided for resident use.Entrance, exits and sidewalks free of impediments.Impediments.1 operable non-pay phone.Impediments.Impediments.1 drinking fountain per CSU accessible to all residents.Impediments.Impediments.1 drinking fountain per CSU accessible to all residents.Impediments.Impediments.Lighting must be incapable of manipulation or removal.Impediments.Impediments.Lighting fixtures must be recessed or tamper proof (ex. lexan).Impediments.Impediments.Water temp maintained between 110-120 F degrees (43-48 C)Impediments.Impediments.Unbreakable mirrors.Impediments.Impediments.Impediments.82-31-23 Environment of CareImpediments.Impediments.Impediments.Blind spots addressed. unbreakable mirrors.Impediments.Impediments.Impediments.Doors shall be locked from within and shall be capable of swinging outward.Impediments.Impediments.Lighting must be sufficient for reading.Impediments.Impediments.Impediments.Lighting must be sufficient for reading.Impediments.Impediment		
individuals.	Additional Requirements	
Laundry facilities provided for resident use.       Entrance, exits and sidewalks free of impediments.         I operable non-pay phone.       I         1 drinking fountain per CSU accessible to all residents.       I         Hardware must be incapable of manipulation or removal.       I         Lighting fixtures must be recessed or tamper proof (ex. lexan).       I         Water temp maintained between 110-120 F degrees       I         43-48 C)       I         Unbreakable mirrors.       I         B2-31-23 Environment of Care       I         The ceilings and air distribution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.       I         Blind spots addressed. unbreakable mirrors.       Doors shall be locked from within and shall be capable of swinging outward.       I         Electronic locks shall be equipped with a manual key override.       I       I         Hardware must be incapable of manipulation or removal.       I       I         Lighting fixtures must be incapable of manipulation or removal.       I       I         Lighting fixtures must be incapable of manipulation or removal.       I       I         Lighting fixtures must be incapable of manipulation or removal.       I       I         Lighting fixtures must be sufficient for reading.       I       I         Lighting must be suffici	Locked storage for valuable and belongings of all	
Entrance, exits and sidewalks free of impediments.       Impediate in the impediments.         1 operable non-pay phone.       Impediate in the impediments.         1 drinking fountain per CSU accessible to all residents.       Impediate in the impediments.         Hardware must be incapable of manipulation or removal.       Impediate in the impediments.         Lighting must be sufficient for reading.       Impediate in the impediments.         Lighting fixtures must be recessed or tamper proof (ex. lexan).       Impediate in the impediments.         Water temp maintained between 110-120 F degrees       Impediate in the impediments.         (43-48 C)       Impediate in the impediments.         Unbreakable mirrors.       Impediate in the impediments.         82-31-23 Environment of Care       Impediate in the impediments.         The ceilings and air distribution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.       Impediate in the impediments.         Blind spots addressed. unbreakable mirrors.       Impediate in the impediments.       Impediate in the impediments.         Doors shall be locked from within and shall be capable of swinging outward.       Impediate in the impediment or removal.       Impediate in the impediment or removal.         Lighting fixtures must be incapable of manipulation or removal.       Impediate in the impediment or removal.       Impediate in the impediment or removal.         Lighting fixtures must be	individuals.	
1 operable non-pay phone.       1         1 drinking fountain per CSU accessible to all residents.       1         Hardware must be incapable of manipulation or removal.       1         Lighting must be sufficient for reading.       1         Lighting fixtures must be recessed or tamper proof (ex. lexan).       1         Water temp maintained between 110-120 F degrees (43-48 C)       1         Unbreakable mirrors.       2         82-3-1-23 Environment of Care       1         The ceilings and air distribution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.       1         Blind spots addressed. unbreakable mirrors.       2         Doors shall be locked from within and shall be capable of swinging outward.       2         Electronic locks shall be equipped with a manual key override.       2         Hardware must be incapable of manipulation or removal.       2         Lighting must be sufficient for reading.       2         Lighting fixtures must be recessed or tamper proof (ex. lexan).       2         Water temp maintained between 110-120 F degrees       2	Laundry facilities provided for resident use.	
1 drinking fountain per CSU accessible to all       residents.         Hardware must be incapable of manipulation or       removal.         Lighting must be sufficient for reading.       Lighting fixtures must be recessed or tamper proof         (ex. lexan).       (ex. lexan).         Water temp maintained between 110-120 F degrees       (43-48 C)         Unbreakable mirrors.       2000         82-3-1-23 Environment of Care       10000         The ceilings and air distribution devices, light       100000         fixtures, sprinkler heads, and other apparatus shall be       1000000000000000000000000000000000000	Entrance, exits and sidewalks free of impediments.	
1 drinking fountain per CSU accessible to all       residents.         Hardware must be incapable of manipulation or       removal.         Lighting must be sufficient for reading.       Lighting fixtures must be recessed or tamper proof         (ex. lexan).       (ex. lexan).         Water temp maintained between 110-120 F degrees       (43-48 C)         Unbreakable mirrors.       2000         82-3-1-23 Environment of Care       10000         The ceilings and air distribution devices, light       100000         fixtures, sprinkler heads, and other apparatus shall be       1000000000000000000000000000000000000	1 operable non-pay phone.	
residents.		
removal. Lighting must be sufficient for reading. Lighting fixtures must be recessed or tamper proof (ex. lexan). Water temp maintained between 110-120 F degrees (43-48 C) Unbreakable mirrors. 82-3-1-23 Environment of Care The ceilings and air distribution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant. Blind spots addressed. unbreakable mirrors. Doors shall be locked from within and shall be capable of swinging outward. Electronic locks shall be equipped with a manual key override. Hardware must be incapable of manipulation or removal. Lighting must be sufficient for reading. Lighting fixtures must be recessed or tamper proof (ex. lexan). Water temp maintained between 110-120 F degrees		
removal. Lighting must be sufficient for reading. Lighting fixtures must be recessed or tamper proof (ex. lexan). Water temp maintained between 110-120 F degrees (43-48 C) Unbreakable mirrors. 82-3-1-23 Environment of Care The ceilings and air distribution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant. Blind spots addressed. unbreakable mirrors. Doors shall be locked from within and shall be capable of swinging outward. Electronic locks shall be equipped with a manual key override. Hardware must be incapable of manipulation or removal. Lighting must be sufficient for reading. Lighting fixtures must be recessed or tamper proof (ex. lexan). Water temp maintained between 110-120 F degrees	Hardware must be incapable of manipulation or	
Lighting fixtures must be recessed or tamper proof       (ex. lexan).         Water temp maintained between 110-120 F degrees       (43-48 C)         Unbreakable mirrors.       20 <b>82-31-23 Environment of Care</b> 10         The ceilings and air distribution devices, light       10         fixtures, sprinkler heads, and other apparatus shall be       10         tamper-resistant.       10         Blind spots addressed. unbreakable mirrors.       10         Doors shall be locked from within and shall be       10         capable of swinging outward.       10         Electronic locks shall be equipped with a manual key override.       10         Hardware must be incapable of manipulation or removal.       11         Lighting must be sufficient for reading.       11         Lighting fixtures must be recessed or tamper proof (ex. lexan).       10         Water temp maintained between 110-120 F degrees       10	· · ·	
(ex. lexan).       Image: Constraint of the system of the sy	Lighting must be sufficient for reading.	
(ex. lexan).       Image: Constraint of the system of the sy	· · ·	
(43-48 C)       Unbreakable mirrors. <b>82-3-1-23 Environment of Care</b> Image: Constraint of the second s		
Unbreakable mirrors.Image: Constraint of the ceiling solution of the ceiling solution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.Image: Constraint of the ceiling solution of the ceili	Water temp maintained between 110-120 F degrees	
82-3-1-23 Environment of Care       Image: Care State St	(43-48 C)	
The ceilings and air distribution devices, light fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.Image: Construct of the systemBlind spots addressed. unbreakable mirrors.Image: Construct of the systemImage: Construct of the systemDoors shall be locked from within and shall be capable of swinging outward.Image: Construct of the systemImage: Construct of the systemElectronic locks shall be equipped with a manual key override.Image: Construct of the systemImage: Construct of the systemHardware must be incapable of manipulation or removal.Image: Construct of the systemImage: Construct of the systemLighting must be sufficient for reading.Image: Construct of the systemImage: Construct of the systemLighting fixtures must be recessed or tamper proof (ex. lexan).Image: Construct of the systemImage: Construct of the systemWater temp maintained between 110-120 F degreesImage: Construct of the systemImage: Construct of the system	Unbreakable mirrors.	
fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.Image: constraint of the systemBlind spots addressed. unbreakable mirrors.Image: constraint of the systemDoors shall be locked from within and shall be capable of swinging outward.Image: constraint of the systemElectronic locks shall be equipped with a manual key override.Image: constraint of the systemHardware must be incapable of manipulation or removal.Image: constraint of the systemLighting must be sufficient for reading.Image: constraint of the systemLighting fixtures must be recessed or tamper proof (ex. lexan).Image: constraint of the systemWater temp maintained between 110-120 F degreesImage: constraint of the system	82-3-1-23 Environment of Care	
fixtures, sprinkler heads, and other apparatus shall be tamper-resistant.Image: constraint of the systemBlind spots addressed. unbreakable mirrors.Image: constraint of the systemDoors shall be locked from within and shall be capable of swinging outward.Image: constraint of the systemElectronic locks shall be equipped with a manual key override.Image: constraint of the systemHardware must be incapable of manipulation or removal.Image: constraint of the systemLighting must be sufficient for reading.Image: constraint of the systemLighting fixtures must be recessed or tamper proof (ex. lexan).Image: constraint of the systemWater temp maintained between 110-120 F degreesImage: constraint of the system	The ceilings and air distribution devices, light	
Blind spots addressed. unbreakable mirrors.	fixtures, sprinkler heads, and other apparatus shall be	
Blind spots addressed. unbreakable mirrors.		
Doors shall be locked from within and shall be capable of swinging outward.Image: Constraint of the systemElectronic locks shall be equipped with a manual key override.Image: Constraint of the systemHardware must be incapable of manipulation or removal.Image: Constraint of the systemLighting must be sufficient for reading.Image: Constraint of the systemLighting fixtures must be recessed or tamper proof (ex. lexan).Image: Constraint of the systemWater temp maintained between 110-120 F degreesImage: Constraint of the system	<u>^</u>	
Electronic locks shall be equipped with a manual key override.       Image: Constraint of the state of the s		
Electronic locks shall be equipped with a manual key override.       Image: Constraint of the state of the s	capable of swinging outward.	
Hardware must be incapable of manipulation or removal.Image: Constraint of the sufficient of the sufficient for reading.Lighting must be sufficient for reading.Image: Constraint of the sufficient of the suffi		
removal. Lighting must be sufficient for reading. Lighting fixtures must be recessed or tamper proof (ex. lexan). Water temp maintained between 110-120 F degrees		
removal. Lighting must be sufficient for reading. Lighting fixtures must be recessed or tamper proof (ex. lexan). Water temp maintained between 110-120 F degrees	Hardware must be incapable of manipulation or	
Lighting fixtures must be recessed or tamper proof       (ex. lexan).         Water temp maintained between 110-120 F degrees       (ex. lexan)	· · ·	
Lighting fixtures must be recessed or tamper proof       (ex. lexan).         Water temp maintained between 110-120 F degrees       (ex. lexan)	Lighting must be sufficient for reading.	
(ex. lexan). Water temp maintained between 110-120 F degrees		
Water temp maintained between 110-120 F degrees		
Unbreakable mirrors.	Unbreakable mirrors.	